



Product Information

- PVC Cards
- Blank White
- 30 MIL
- Rewritable Blue (C5101) or Black (C5201)

PRINT TEMPORARY OR UPDATABLE CARDS

These cards, thanks to a specific material, are re-writable and don't require any ribbon. The information can be erased in order to note down another printing elements on the same card. They are available with black or blue monochrome printing.

ADVANTAGES

Evolis PVC rewritable cards bring you flexibility as you can deliver a new card anytime it is required, a cost effective solution (no ribbon needed), and help to reduce the environment footprint.

The same card can be reused and reprinted up to 500 times.

These cards are very useful in a fidelity program, for example, when the data change every customer's visit. You don't have to create a new card when the writing information is changing.

Tested and validated by Evolis R&D and Quality departments, these consumables bring you printing quality and reliability.

GENERAL SPECIFICATIONS

Rewrite technology:

The rewritable printing technology does not require any ribbon to personalize cards. The card itself holds a thermo sensitive material that turns visible when heated to a temperature of 356° F (180° C) and then rapidly cooled. The application of a lower temperature, generally in the $230-320^{\circ}$ F ($110-160^{\circ}$ C) range, will erase any color pattern.

Features:

- Cards in PVC with an Overlay PET Thermo Re-Writable Blank white
- Compliant with ISO CR-80 (ISO 7810) standards
- Dimension: 85.6 mm Length x 54 mm Width
- Thickness: 0.76 mm / 30 MIL
- Available in two printing colors, Blue (C5101) and Black (C5201)
- Cards lifespan: Up to 500 print

PART#	PACKAGE	PRINTING COLOR	TATTOO ² RW
C5101	1 box of 100 cards	BLUE	•
C5201	1 box of 100 cards	BLACK	•

Storage Information:

The cards shall be capable of functioning for up to 2 years after purchase if stored in a cool, dry environment and having remained unopened from the original packaging. Temperature of storage must be between 15-30°C and at RH between 10-60%. Once opened, avoid dust, direct sunlight, high humidity and high temperatures. Do not place near solvent or other chemicals.

INSTRUCTIONS FOR USE

In order to optimize the printing quality and card durability:

• Do not use cards that have been damaged, folded or dropped on the floor.